

Gillibrand Industrial Sands-Simi Valley-CA

## Product Data Sheet

### # 12 Silver Sand

*In compliance with ANSI/NFS 61 for Water Filtration*

*California ARB Certified for Outdoor Sandblasting*

#### Typical Physical Properties

<b>Color:</b>	Light tan
<b>Grain Shape:</b>	Sub-angular
<b>Hardness, Moh</b>	6.5
<b>Moisture Content(% by wt):</b>	< 0.1
<b>Bulk Density :</b>	96 lbs/ft <sup>3</sup> (1536 kg/m <sup>3</sup> )
<b>Specific Gravity:</b>	2.6
<b>Effective Size:</b>	1.20-1.40
<b>Uniformity Coefficient:</b>	1.30-1.60

#### Typical Sieve Analysis

US Sieve Size No.	% Retained on Sieve	Range
8	1	0-5
10	10	5-25
12	53	40-65
16	33	15-45
20	1	0-5
30	1	0-2

#### Disclaimer:

The information presented in this Product Data Sheet lists typical properties of the described product. By this Product Data Sheet, P.W. Gillibrand Co., Inc. makes no warranty, expressed or implied, of fitness for any purpose.

#### Warning:

This product contains crystalline silica (Quartz), known to the State of California to cause cancer. For additional information on the potential health effects of crystalline silica, please see the P.W. Gillibrand Co., Inc. Safety Data Sheet (SDS).