

LOCATION: San Juan Capistrano

DATE:07/01/25

CALTEGA Golf Sand

TYPICAL SIEVE ANALYSIS

US			Cum %	Ind %	USGA Greens
SIEVE	mm		Passing	Retained	Recommendation
#10	2.00	Gravel	100	-	≤ 10
#18	1.00	Very Coarse	93.0	7.0	≥ 10
#35	0.50	Coarse	53.0	40.0	≥ 60%
#60	0.25	Medium	5.0	48.0	
#100	0.15	Fine	2.0	3.0	≤ 20
#270	0.05	Very Fine	0.4	1.6	≤ 5
PAN				0.4	≥ 5

Particle Angularity:	Sub Angular - Angular	
Particle Spericity:	Medium	
Bulk Density:	95 lbs/ft ³	
Ksat:	> 40"/hr	
Penetrometer Value:	≥ 2.2 kg/cm ²	
Infiltration Rate: (in/hr)	32.7	
Uniformity Coefficient:	2.1	
D15 (mm):	0.29	
D50 (mm):	0.49	
D85 (mm):	0.87	

The information presented on this report lists typical properties of the described product. By this report P.W. Gillibrand Co., Inc. makes no warranty, expressed or implied, of fitness for any purpose. Values valid for 90 days.

Ph: 805 526 2195